



**HP DuPont Tyvek® Banner is a cost-effective, environmentally-responsible alternative to regular scrim banners; this recyclable, lightweight HDPE Tyvek® banner is easy to grommet, hang or stitch for easy installation<sup>1</sup>.**

**Ideal for mid-volume print service providers (PSPs) looking for a well-priced, lightweight and versatile Tyvek® media**

Brilliant indoor and outdoor banners made with Tyvek® deliver high image quality with high-colour brilliance and waterfast, stay-true colours. Surface treated and doesn't require lamination for outdoor use.

This Tyvek® banner is more versatile than ordinary scrim banners and is recyclable. It fits a range of indoor and outdoor applications. Its strong but lightweight composition is tear-resistant.

A highly durable, recyclable media that fits a wide range of indoor and outdoor applications. This Tyvek® banner resists tears and scratches for reliable indoor and outdoor displays.

<sup>1</sup> Recycling opportunities for this product currently only available in limited areas. Customers should consult local recycling resources for recycling this product.

# HP DuPont Tyvek Banner

## Compatibility

For compatibility information, please refer to the latest Large Format Supplies Compatibility chart on [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies)

For the latest ICC/media profiles, please visit [www.hp.com/go/designjet/supplies](http://www.hp.com/go/designjet/supplies) (click on ICC profiles and select your printer). For non-post script printers see your external RIP vendor.

## Product specifications

Weight	135 g/m <sup>2</sup> per ISO 536 Test Method
Thickness	12 mil/290 microns per ISO 534 Test Method
Opacity	Less than 95% per TAPPI T-425 Test Method
Brightness	97% per TAPPI T-452 Test Method
Whiteness	130 per CIE Ganz 82 Test Method
Lamination	Yes (spray)
Mounting	Grommets, Sewing, Glueing
Finish	Semi-gloss
Tear resistant	MD ≥30 N / CD ≥30 N per ASTM D1004 Test Method
Tensile strength	MD ≥270 N / CD ≥300 N per TAPPI T-494 Test Method
Operating temperature	15 to 100° C
Operating humidity	20 to 80% RH
Lightfastness (Indoor Home or Office)	50 years (with Latex Ink Supplies). For details: <a href="http://www.hp.com/go/supplies/printpermanence">http://www.hp.com/go/supplies/printpermanence</a> .
Low-solvent Ink	
Waterfastness	Water-resistant
Dry time	Instant dry with heating (@ 23°C, 50% RH)
Shelf time	2 years, unopened in original packaging
Storage temperature	0 to 40° C
Storage humidity	5 to 95% RH
Country of origin	Product of United States

Ordering information	Product Numbers	Roll sizes	UPC codes
	CG444A	914 mm x 30.5 m	883585620104
	CG445A	1067 mm x 30.5 m	883585620111
	CG446A	1524 mm x 45.7 m	883585620128
	CG447A	2642 mm x 100.6 m	883585620135

**Warranty** HP large format printing material is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. If for any reason the users are unsatisfied with HP large format printing material they should contact their HP reseller.

© 2008 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For more information about HP Large Format Printing Material,  
visit <http://www.hp.com/go/designjet/supplies>

Published in EMEA 4AA2-1599 EEE

