

Data Sheet

Fujitsu Display B22T-7 LED proGREEN Displays

Advanced display: 54.6 cm (21.5-inch) widescreen
Best ergonomic and energy saving solutions for office applications

The Display B22T-7 LED proGREEN offers best ergonomics and usability for intensive office use with a 4-in-1 stand.

Environment-friendly LED technology with unique, high efficient energy saving solutions like ECO operation mode and ECO standby

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Flexible connectivity with HDMI, DVI and Analog

Representative design with space saving front frame and smart details like discretely integrated speakers



Technical details

Special features

4-in-1 Stand, ECO button, ECO Status LED: 3 colors for 3 modes, Pivot, 24/7 usage, DisplayView™ IT Suite

Ergonomic stand

| | |
|--------------------------------|--------------|
| Stand | 4-in-1 Stand |
| Height adjust range | 130 mm |
| Picture height over desk (min) | 50 mm |
| Rotation to portrait | 90° |
| Tilt angle | -5° / +35° |
| Swivel angle | 340° |

Picture performance

| | |
|-------------------------------|------------------------------|
| Panel and backlit | TN/LED |
| Screen Surface Treatment | Anti-glare, 3H hard coating |
| Contrast - typical | 1000:1 |
| Contrast - advanced | 20,000,000:1 |
| Response time typical | 5 ms |
| Viewing angle (h/v) - typical | 176°/170° CR5:1 |
| Color performance | 16.7 million colors (Hi-FRC) |
| Brightness - typical | 250 cd/m ² |

Size and resolution

| | |
|---------------------------|--|
| Aspect ratio | 16:9 |
| Diagonal Size | 54.6 cm (21.5-inch) |
| Resolution (native) | 1920 x 1080 pixel (recommended) |
| Resolution (interpolated) | 1680 x 1050 pixel, 1440 x 900 pixel, 1366 x 768 pixel, 1280 x 1024 pixel, 1280 x 720 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel |
| Video modes | 1080i/p, 720i/p, 576i/p, 480i/p |
| Picture size | 476 x 268 mm |
| Pixel Pitch | 0.248 mm |

Frequencies

| | |
|---------------------|---|
| Horizontal | 30 - 82 kHz |
| Vertical | 56 - 76 Hz |
| HDMI | 1 x HDMI |
| DVI | 1 x DVI |
| VGA/D-SUB | 1 x D-SUB |
| Audio signal output | 3.5 mm stereo phone jack for head phone |
| Audio signal input | 3.5 mm stereo phone jack |
| Audio sound output | 2 x 1.5 W |
| USB downstream | 4 x USB 2.0 |
| USB upstream | 1 x USB |

Ease-of-use menu

| | |
|-----------------------|---|
| Languages | Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional |
| Brightness / Contrast | Brightness, Contrast, Black level, Auto level |
| Color | sRGB, 6500K, 7500K, 9300K, Native, Custom Color (R,G,B) |
| Image adjust | Clock, Phase, H-Position, V-Position, Expansion |
| Audio | Mute, Volume |
| Information | Model name, S/N, Resolution/mode, Signal input |
| Setup | Input select, Language, DDC-CI, OSD-Timeout, Factory recall |

Power consumption (typical, w/o sound)

| | |
|-----------------|-------|
| Soft switch off | 0.2 W |
| Power save mode | 0.3 W |

| | |
|--|--|
| Operating with EPA settings | 18 W |
| Operating maximum brightness | 22 W |
| Power supply display | integrated |
| Power notes | without sound, without USB |
| Electrical values | |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Protection class | 1 |
| Europe | CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration |
| Model | B22T-7 LED |
| Germany | TÜV GS |
| Russia | GOST |
| USA/Canada | FCC Class B, cUL |
| Australia/New Zealand | C-Tick |
| Japan | VCCI |
| South Korea | KC |
| Argentina | TÜV-S |
| Taiwan | BSMI |
| China | CCC |
| Saudi Arabia | SASO |
| Global | TCO Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions) (planned), ISO9241-307 (Pixel fault class I) |
| Quality and Reliability | |
| MTBF (demonstrated) | 70000 h |
| Dimensions / Weight / Environmental | |
| Dimension without stand (W x D x H) | 516 x 61 x 320 mm |
| Dimension with stand (W x D x H) | 516 x 200 x 339 mm |
| Weight (packed) | 7.0 kg |
| Weight (unpacked) | 5.8 kg |
| Weight (Monitor only) | 3.1 kg |
| Operating ambient temperature | 5 - 35°C |
| Miscellaneous | |
| Miscellaneous | VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock prepared |
| Package content | |
| Display delivered accessories | DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet |
| Display delivered accessories notes | Data cables and audio cable detachable on display |
| Order information | |
| Order Code | S26361-K1453-V160 |
| EAN-No. | 4051554497729 |
| Warranty | |
| Standard Warranty | 3 years |
| Service level | Collect & Return Service (depending on country specific requirements) |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu Display B22T-7 LED proGREEN, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Display B22T-7 LED proGREEN, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/fts/displays>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2013-01-14 CE-EN

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions