



Eaton 9130 Tower UPS

Efficient, reliable and scalable protection for servers, data networks and other IT equipment

Eaton 9130 Tower features and benefits

Increased battery life: Eaton® offers ABM® technology that increases battery service life by 50 percent. ABM uses an advanced, three-stage charging technique and closely monitors battery health to provide advanced notice when batteries need replacement.

More power: The 9130 allows you to connect more devices and leave room for expanding IT systems by providing up to 28 percent more wattage compared to traditional UPSs.

Manageability:

- Load segmentation: Grouped outlets with remote control capability enable IT managers to cycle or shed loads through a webcard interface or based upon a preprogrammed schedule.
- Eaton's Intelligent Power Manager (IPM): IPM software provides network power management, ensuring data and system integrity. With IPM, you can have access to easy, versatile, remote monitoring and management of multiple devices.

LCD interface: The bright, intuitive LCD user interface simplifies UPS monitoring and management. The user-friendly menu allows you to view all critical UPS information in a single view.

Low total cost of ownership: The 9130 can help cut energy usage costs with >95% efficiency rating in high efficiency mode and can provide more real output power per each dollar spent with a 0.9 power factor.

Intelligent Power Software Suite

By integrating the bundled Intelligent Power® Software Suite (IPSS), you can monitor and manage your network power devices. IPSS enables you to:

- Seamlessly integrate with VMware's vCenter™ Server™ virtualization management solution, as well as virtualization platforms such as Citrix® XenServer, Microsoft SCVMM™, Red Hat® and other Xen® open source platforms
- Initiate live migration of virtual machines (VMs) to automatically and transparently migrate them during power disruptions to unaffected devices with systems such as VMware vMotion™ and Microsoft Live Migration
- Gracefully shutdown computers, VMs and host servers during an extended power outage

To learn more, please visit: Eaton.com/intelligentpower



Microsoft Partner Network

Services and support

Eaton provides 24x7 product support. From battery replacement to full UPS service plans, Eaton has one of the top service models in the industry.



Powering Business Worldwide

Front panel overview



- 1 LCD panel
- 2 LED indicators
- 3 Sleek tower design
- 4 Hot swappable batteries
- 5 High efficiency mode
- 6 EBM connector
- 7 Communication slot
- 8 RS-232 port
- 9 USB port

Back panel overview

Model PW9130L1500T-XL



- 10 Standard relay output contact
- 11 Remote Power Off (RPO) connector
- 12 Fan
- 13 Load segment 1 with (3) 5-15R
- 14 Load segment 2 with (3) 5-15R
- 15 6-foot line cord with 5-15P

9130 Tower model selection guide

Catalog number	Power rating (VA/watts)	Input	Output	Dimensions (HxWxD, in.)	Weight (lb.)
North American models: 120V, 50/60 Hz					
PW9130L700T ³	700/630	5-15P ¹	(6) 5-15R	9.1 x 6.3 x 13.8	26.9
PW9130L1000T-XL	1000/900	5-15P ¹	(6) 5-15R	9.1 x 6.3 x 15.0	32.0
PW9130L1500T-XL	1500/1350	5-15P ¹	(6) 5-15R	9.1 x 6.3 x 16.9	41.9
PW9130L2000T-XL	2000/1800	5-20P ¹	(1) L5-20R, (4) 5-20R	12.8 x 8.4 x 16.1	76.1
PW9130L3000T-XL	3000/2700	L5-30P ¹	(4) 5-20R, (1) L5-30R	12.8 x 8.4 x 16.1	76.1
Global models: 208V, 50/60 Hz					
PW9130G1000T-XL	1000/900	L6-20P ²	(1) L6-20R, (2) 6-20R	9.1 x 6.3 x 15.0	32.0
PW9130G2000T-XL	2000/1800	L6-20P ²	(1) L6-20R, (4) 6-20R	12.8 x 8.4 x 16.1	76.1
PW9130G2000T-XLEU	2000/1800	L6-20P ²	(8) C13, (1) C19	12.8 x 8.4 x 16.1	76.1
PW9130G3000T-XL	3000/2700	L6-20P ²	(1) L6-30R, (1) L6-20R, (2) 6-20R	12.8 x 8.4 x 16.1	76.1
PW9130G3000T-XLEU	3000/2700	L6-20P ²	(8) C13, (1) C19	12.8 x 8.4 x 16.1	76.1
International models: 230V, 50/60 Hz					
PW9130i700T ³	700/630	C14	(6) C13	9.1 x 6.3 x 13.8	26.9
PW9130i1000T-XL	1000/900	C14	(6) C13	9.1 x 6.3 x 15.0	32.0
PW9130i1500T-XL	1500/1350	C14	(6) C13	9.1 x 6.3 x 16.9	41.9
PW9130i2000T-XL	2000/1800	C14	(8) C13, (1) C19	12.8 x 8.4 x 16.1	76.1
PW9130i3000T-XL	3000/2700	C20	(8) C13, (1) C19	12.8 x 8.4 x 16.1	76.1
Extended battery modules					
PW9130N1000T-EBM	Works with 1000 VA model, where available			9.1 x 6.3 x 15.0	40.8
PW9130N1500T-EBM	Works with 1500 VA model			9.1 x 6.3 x 16.9	53.6
PW9130N3000T-EBM	Works with 2000/3000 VA models, where available			12.8 x 8.4 x 16.1	110.3

1. Input cord length is 6 ft.

2. C20, w/ detachable L6-20P.

3. 700 VA models cannot be configured with extended battery modules (EBMs).

Additional notes:

When high voltage 9130 is used at 208V, derate power by 10% and 20% at 200V

When low voltage 9130 is used at 110V, derate power by 10% and 20% at 100V

For complete battery runtime information and to interact with the 9130 Tower UPS, please visit: Eaton.com/9130

Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
Eaton.com

© 2014 Eaton
All Rights Reserved
Printed in USA
9130TFXA
September 2014

Eaton, ABM and Intelligent Power are registered trademarks of Eaton.

All other trademarks are property of their respective owners.