



## Philips Signage Solutions Video Wall Display

- 47"
- Direct LED Backlight
- Full HD

**Signage**Solutions

**BDL4776XL**

## Create the most stunning video walls

with this LED zero-bezel display

Create the most mesmerising video walls with our range of video wall models. With practically zero bezel and stunning full HD picture quality, you're sure to create the most memorable visual experience.

### Optimised for public viewing

- Bezel-less design for stunning video walls

### High picture and video quality

- Advanced Colour Calibration

### Operational flexibility

- Direct LED Backlight
- Designed for 24/7 operation
- Portrait mode operability
- Open Pluggable Specification Slot
- Smart Control Software Suite
- DVI Daisy Chain
- Keep your content up and running with Failover
- IR Pass-through
- Display Port for faster graphics support
- Network Controllability: RJ45

**PHILIPS**

# Highlights

## Direct LED Backlight

Enjoy superior light uniformity with a direct LED backlight, which gives you even greater contrast ratios. Purer whites bring an even wider colour gamut, enhancing the colour rendering and making your viewing experience more enjoyable than ever before. And with substantially lower power consumption, your overall TCO is lower too.

## Bezel-less design

Create the most stunning video walls with zero-bezel displays. Configurable in a formation of up to 5 x 5 displays, and with some of the narrowest mullions in the industry. You will hardly notice the gap between the pictures, giving you the most incredible and memorable visual experience.

## Advanced Colour Calibration

Ensure a uniform colour across all displays installed in your network thanks to our advanced colour calibration tool. This tool will automatically adjust all displays in your signage application to ensure the ultimate in colour consistency to give your audience the most memorable visual experience.

## OPS Slot

Developed for the Digital Signage market, the Open Pluggable Specification (OPS) slot is designed to make changing or upgrading your media player mere child's play. Simply plug your media player in to the display and you're ready. No matter whether you have an entry

level, mid-range or high-end media player, OPS is fully compatible bringing you a lower TCO over the longer term.

## Smart Control

Control and manage all of the signage displays on your network with this powerful software tool, which allows you to change the settings of your display centrally via an RJ45 or RS232 connection. Smart Control allows you to set the video input, modify the colour settings, set the display's ID when creating video walls and even diagnose each display's status, giving you all the power you need to manage your displays from one central location.

## DVI Daisy Chain

Create a digital video wall of up to 25 displays in a 5 x 5 configuration with a DVI daisy chain. Simply connect the DVI Out port to a DVI in of another display to create the most stunning video wall experience around.

## Failover

Keeping your content up and running is critical for demanding commercial applications. While it is unlikely you will face a content disaster, Failover provides 24/7 protection with a revolutionary technology that plays back-up content on screen in the event of a media player failure. Failover automatically kicks in when the primary input fails. Simply select a primary input connection and a Failover connection and you're ready for instant protection.

## IR Pass-through

Control all displays in your signage network through one single remote control, via the primary display. Simple and convenient, this means you don't have to worry about other displays changing configuration settings when using your remote control unit.

## RJ45

Simple management of your display is available thanks to the introduction of a LAN (RJ45) port. You can configure each display or find out the status of each device quickly and conveniently via an RJ45 connection.

## Portrait mounting possible

This display can also be safely and reliably mounted in portrait position.

## Display Port

Enjoy crystal-clear images with the high-bandwidth graphics support of the Display Port. As well as transmitting full high-definition video, the Display Port will also transmit audio, thus, eliminating the need for extra cables.

## Designed for 24/7 operation

Because business never sleeps, our signage displays are designed for 24/7 use. Taking advantage of superior components to ensure a higher level of quality, you can count on this range of models for complete around-the-clock reliability.



# Specifications

## Picture/Display

- Diagonal screen size: 46.9 inch / 119.3 cm
- Panel resolution: 1920 x 1080p
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 500 cd/m<sup>2</sup>
- Contrast ratio (typical): 1400:1
- Response time (typical): 12 ms
- Aspect ratio: 16:9
- Pixel pitch: 0.54 x 0.54 mm
- Display colours: 16.7 million
- Viewing Angle (H / V): 178 / 178 degree
- Picture enhancement: 3/2 - 2/2 motion pull down, Motion compens. deinterlacing, Progressive scan, Dynamic contrast enhancement

## Connectivity

- PC: VGA-in D-Sub 15HD, VGA-out D-Sub 15HD, RJ45, RS232 D-Sub9, RS232 D-sub9 output, 3.5 mm PC audio input x 1, DVI-D x 1
- AV input: Component (BNC) x 1, HDMI x 1, IR in
- Other connections: Display Port, DVI Out, IR out, OPS
- AV output: Audio (L/R) x 1

## Supported Display Resolution

### Computer formats

Resolution	Refresh rate
640 x 480	60, 67, 72, 75 Hz
800 x 600	56, 60, 72, 75 Hz
1024 x 768	60 Hz
1280 x 768	60 Hz
1280 x 800	60 Hz
1280 x 1024	60 Hz
1360 x 768	60 Hz
1366 x 768	60 Hz
1440 x 900	60 Hz
1600 x 1200	60 Hz
1920 x 1080	60 Hz
1920 x 1200	60 Hz

### Video formats

Resolution	Refresh rate
480i	60 Hz
480p	60 Hz
576p	50 Hz
576i	50 Hz
720p	50, 60 Hz
1080i	50, 60 Hz
1080p	50, 60 Hz

## Convenience

- Placement: Portrait, Landscape
- Tiled Matrix: Up to 5 x 5
- Picture in picture: PBP, PIP, POP

- Signal Loop Through: DVI, VGA, RS232, IR Loop through
- Keyboard control: Hidden, Lockable
- Remote control signal: Lockable
- Energy-saving functions: Smart Power
- Packaging: Reusable box
- Network controllable: RS232, RJ45
- OSD Languages: Dutch, English, French, German, Italian, Polish, Russian, Simplified Chinese, Spanish, Turkish
- Picture performance: Advanced colour control
- Safety control functions: Heat Control, Temperature Sensor

## Sound

- Built-in speakers: 2 x 10 W

## Dimensions

- Set dimensions (W x H x D): 1046.8 x 591.6 x 109.0 mm
- Product weight: 25.5 kg
- Bezel width (A to A): 6.3 mm
- Bezel width (L/T, R/B): 3.9 mm, 2.4 mm
- VESA Mount: 400 x 400 mm, 400 x 200 mm, 200 x 200 mm
- Smart Insert mount: 100 x 100 mm, 100 x 200 mm

## Power

- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- Consumption (On mode): 110.5 W (EnergyStar 6.0 test method)
- Standby power consumption: <0.5 W

## Operating conditions

- Temperature range (operation): 0 ~ 50 °C
- Temperature range (storage): -20 ~ 60 °C
- Altitude: 0 ~ 5000 m
- Relative humidity: 10 ~ 90 %
- MTBF: 60,000 hour(s)

## Accessories

- Included accessories: Remote Control, Batteries for remote control, AC Power Cord, VGA cable, User manual on CD-ROM, Quick start guide
- Stand: BM06511 (Optional)

## Miscellaneous

- On-Screen Display Languages: English, French, Spanish, German, Italian, Polish, Turkish, Russian, Simplified Chinese
- Regulatory approvals: CE, FCC, Class B, UL/cUL, CCC, RoHS, GOST
- Warranty: 3-year warranty



Issue date 2013-08-05

Version: 1.0.1

12 NC: 8670 000 96463  
EAN: 87 12581 66299 8

© 2013 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)