

Overview

Models

HP X131 10G X2 SC SR Transceiver	J8436A
HP X131 10G X2 SC LR Transceiver	J8437A
HP X131 10G X2 SC ER Transceiver	J8438A
HP X131 10G X2 CX4 Transceiver	J8440C
HP X131 10G X2 SC LRM Transceiver	J9144A



Technical Specifications

HP X131 10G X2 SC SR Transceiver (J8436A)	Ports	1 SC 10-GbE port (IEEE 802.3ae Type 10GBASE-SR); Duplex: full only
	Connectivity	Connector type SC
HP X131 10G X2 SC SR Transceiver: An X2 format 10-gigabit transceiver with SC connectors using SR technology.	Physical characteristics	Wavelength 850 nm
		Dimensions 3.48(d) x 1.42(w) x 0.43(h) in. (8.84 x 3.61 x 1.09 cm)
	Environment	Weight 0.35 lb. (0.16 kg)
		Transceiver form factor X2
		Operating temperature 32°F to 158°F (0°C to 70°C)
		Operating relative humidity 0% to 95%, noncondensing
	Electrical characteristics	Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)
		Nonoperating/Storage relative humidity 0% to 95%, noncondensing
		Altitude up to 10,000 ft. (3 km)
		Power consumption typical 1.7 W
Cabling	Power consumption maximum 2.4 W	
	Cable type:: 62.5/125 μm or 50/125 μm (core/cladding) graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;	
	Maximum distance: <ul style="list-style-type: none">• 2-26m with 62.5 μm multimode cable @ 160 MHz*km• 2-33m with 62.5 μm multimode cable @ 200 MHz*km• 2-66m with 50 μm multimode cable @ 400 MHz*km• 2-82m with 50 μm multimode cable @ 500 MHz*km• 2-300m with 50 μm multimode cable @ 2000 MHz*km	
	Cable length 2-300m	
	Fiber type Multi Mode	
Notes	For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended.	
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	



Technical Specifications

HP X131 10G X2 SC LR Transceiver (J8437A)	Ports	1 SC 10-GbE port (IEEE 802.3ae Type 10GBASE-LR); Duplex: full only
	Connectivity	Connector type SC
An X2 form-factor transceiver that supports the 10-Gigabit LR standard, providing 10-Gigabit connectivity up to 10 km on single-mode fiber.	Physical characteristics	Wavelength 1310 nm
		Dimensions 3.48(d) x 1.42(w) x 0.43(h) in. (8.84 x 3.61 x 1.09 cm)
Environment	Weight 0.35 lb. (0.16 kg)	
	Transceiver form factor X2	
	Operating temperature 32°F to 104°F (0°C to 40°C)	
	Operating relative humidity 15% to 95%, noncondensing	
Electrical characteristics	Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)	
	Altitude up to 10,000 ft. (3 km)	
	Power consumption typical 2 W	
Cabling	Power consumption maximum 3 W	
	Cable type:: Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;	
	Maximum distance: <ul style="list-style-type: none">• 10 km	
Notes	Cable length 2m to 10km with 9/125 μm single-mode cable	
	Fiber type Single Mode	
Services	Conditioning patch cord cables are not supported For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	



Technical Specifications

HP X131 10G X2 SC ER Transceiver (J8438A)	Ports	1 SC 10-GbE port (IEEE 802.3ae Type 10GBASE-ER); Duplex: full only
	Connectivity	Connector type SC
HP X131 10G X2 SC ER Transceiver: An X2 format 10-gigabit transceiver with SC connectors using ER technology.	Physical characteristics	Wavelength 1550 nm
		Dimensions 3.48(d) x 1.42(w) x 0.43(h) in. (8.84 x 3.61 x 1.09 cm)
	Environment	Weight 0.35 lb. (0.16 kg)
		Transceiver form factor X2
	Electrical characteristics	Operating temperature 32°F to 104°F (0°C to 40°C)
		Operating relative humidity 15% to 95%, noncondensing
	Cabling	Power consumption typical 3 W
		Power consumption maximum 4.5 W
	Notes	Cable type:: Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;
		Cable length 2m to 30km (max 40km on engineered links)
	Services	Fiber type Single Mode
		Conditioning patch cord cables are not supported For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended.
Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

HP X131 10G X2 CX4 Transceiver (J8440C)	Ports	1 CX4 10-GbE port (IEEE 802.3ak Type 10GBASE-CX4); Duplex: full only
	Connectivity	Connector type CX4
HP X131 10G X2 CX4 Transceiver: An X2 format 10-gigabit CX4 transceiver.	Physical characteristics	Dimensions 3.54(d) x 1.42(w) x 0.53(h) in. (8.99 x 3.61 x 1.35 cm)
		Weight 0.18 lb. (0.08 kg)
	Environment	Transceiver form factor X2
		Operating temperature 32°F to 131°F (0°C to 55°C)
	Electrical characteristics	Operating relative humidity 15% to 95%, noncondensing
		Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)
		Altitude up to 10,000 ft. (3 km)
		Power consumption typical 1.0 W
		Power consumption maximum 3.3 W



Technical Specifications

Cabling	Maximum distance: <ul style="list-style-type: none"> • 15m with CX4 cables • 300m with optical media converter and multimode fiber cable
Notes	Connector: CX4; Duplex: full Use CX4 10-GbE cable (0.5-15 m) or HP X130 CX4 Optical Media Converter (J8439A). For suggested vendors of CX4 cables, please see the "Cabling" answers on the "HP 10-GbE Transceivers" FAQs Web page. Optical Media Converter (OMC) J8439A is not supported on the C version as the power supply for the OMC was removed in this design.
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X131 10G X2 SC LRM Ports Transceiver (J9144A)

An X2 form-factor transceiver that supports the 10-Gigabit LRM standard, providing 10-Gigabit connectivity up to 220 m on legacy multimode fiber.

Physical characteristics	Ports	1 SC 10-GbE port (IEEE 802.3aq Type 10GBASE-LRM); Duplex: full only
Environment	Dimensions	3.54(d) x 1.59(w) x 0.7(h) in. (9.0 x 4.05 x 1.78 cm)
Electrical characteristics	Weight	0.35 lb. (0.16 kg)
Cabling	Transceiver form factor	X2
Notes	Operating temperature	32°F to 158°F (0°C to 70°C)
	Operating relative humidity	0% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 185°F (-40°C to 85°C)
	Altitude	up to 10,000 ft. (3 km)
	Power consumption typical	3.2 W
	Power consumption maximum	4.2 W
	Cabling	Cable type: 62.5/125 μ m or 50/125 μ m (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively (a mode conditioning patch cord may be needed in some multimode fiber installations); Maximum distance: <ul style="list-style-type: none"> • 0.5-220m with 62.5 μm multimode cable @ 160/500 MHz*km • 0.5-220m with 62.5 μm multimode cable @ 200/500 MHz*km • 0.5-100m with 50 μm multimode cable @ 400/400 MHz*km • 0.5-220m with 50 μm multimode cable @ 500/500 MHz*km • 0.5-220m with 50 μm multimode cable @ 1500/500 MHz*km
		Cable length .5m to 220m
		Fiber type Multi Mode
		Wavelength: 1310nm For OM3 cable (50 μ m multimode @ 1500/500 MHz*km), a mode-conditioning patch cord is not required. Other multimode cables may



Technical Specifications

require mode-conditioning patch cords to achieve the maximum distances listed above.

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J9144A 10-GbE X2-SC LRM Optic" on the "HP 10-GbE Transceivers" Manuals Web page.

Power Consumption: 4W Max

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit www.hp.com/networking

© Copyright 2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

